

# Technical information

## Blue Circle Postcrete PRODUCT DATA SHEET

### Blue Circle POSTCRETE

A ready-to-use blend of selected sand, cement and additives formulated for fixing wooden, concrete and metal posts.

#### USES

To fix all types of wood, metal and concrete posts.

#### DESCRIPTION

Blue Circle Postcrete is ready to use. No mixing is required.

#### PACKAGING

Blue Circle Postcrete is packed in weatherproof 20kg plastic packaging.

#### STORAGE


Blue Circle Postcrete is a cement-based material and should be handled and stored with care. This product may be stored, unopened in either indoor or outdoor conditions. Information on the maximum storage period can be found on the bag.

#### CLEANING

All equipment should be cleaned with water. Do not flush down drains.

#### AVAILABILITY

Blue Circle Postcrete is available throughout the United Kingdom. Blue Circle Postcrete is supplied in 20 kg plastic bags.



#### SITWORK

For the best results follow these instructions:

1. Dig a hole relevant to post size - three times wider than the post and as deep as 1/3 of fence heights above the ground.
2. Fill the hole with water to a third of the depth.
3. Pour in Blue Circle Postcrete evenly around post until no standing water is visible (powder completely covers water surface). Sprinkle water on top of powder.
4. Position and level post as required. Setting will take place in 5 to 10 minutes.
5. When set, cover top of hole with soil or grass.
6. You can fix fence panel right after the initial 10 minutes of post setting time.

Do not mix Blue Circle Postcrete with water by hand or machine. Please consult with the table on the reverse for guidance on the quantity of Blue Circle Postcrete to use or alternatively go to [www.tarmac-bluecircle.co.uk/product/postcrete-trade/](http://www.tarmac-bluecircle.co.uk/product/postcrete-trade/)

# Technical information



## CONDITIONS OF USE

- Blue Circle Postcrete may be used for the purposes of fixing domestic posts
- Blue Circle Postcrete may be used for fixing decking posts, rotary washing lines and small/medium sized gateposts (less than 1.0m width gate)
- Blue Circle Postcrete may not be used for general concreting, screeds, mortar, grout or render
- If a specified compressive strength is required, Blue Circle Postcrete should not be used
- Normal site practice to the relevant British and European Standards should always apply. Tarmac Cement cannot be held responsible where workmanship has not been carried out in accordance with good practice
- Manual handling should comply with The Manual Handling Operations Regulations 1992.

## HEALTH AND SAFETY

Contact between cement powder and body fluids (eg, sweat and eye fluids) may cause irritation, dermatitis or burns. For further information, including control of soluble hexavalent chromium, refer to the appropriate Tarmac Cement Health and Safety Information Sheets.

## TECHNICAL SUPPORT

Further information and advice on this product and the full range of Tarmac Cement products can be obtained through the contact listed below.

For more details contact:  
[customerservice@tarmac.com](mailto:customerservice@tarmac.com)

Post size	Hole size (Width x depth)	No. of bags required
<b>Round 5cm (2")</b>	15cm(6") x 30cm(12")	¼ bag
	15cm(6") x 45cm(18")	½ bag
	15cm(6") x 60cm(24")	½ bag
	20cm(8") x 30cm(12")	½ bag
	20cm(8") x 45cm(18")	¾ bag
	20cm(8") x 60cm(24")	1 bag
<b>Square 7.5cm (3")</b>	15cm(6") x 45cm(18")	½ bag
	15cm(6") x 60cm(24")	½ bag
	15cm(6") x 75cm(30")	¾ bag
	20cm(8") x 45cm(18")	¾ bag
	20cm(8") x 60cm(24")	¾ bag
	20cm(8") x 75cm(30")	1 bag
	25cm(10") x 45cm(18")	1 ½ bags
	25cm(10") x 60cm(24")	1 ½ bags
	25cm(10") x 75cm(30")	1 ¾ bags
	30cm(12") x 45cm(18")	2 bags
<b>Square 10cm (4")</b>	20cm(8") x 45cm(18")	¾ bag
	20cm(8") x 60cm(24")	¾ bag
	20cm(8") x 75cm(30")	1 bag
	25cm(10") x 45cm(18")	1 ¼ bags
	25cm(10") x 60cm(24")	1 ½ bags
	25cm(10") x 75cm(30")	1 ¾ bags
	30cm(12") x 45cm(18")	1 ¾ bags
	30cm(12") x 60cm(24")	2 bags
	30cm(12") x 75cm(30")	2 ½ bags

The information given in this technical data sheet is based on our current knowledge and is intended to provide general notes on our products and their uses. Tarmac endeavour to ensure that the information given is accurate, but accept no liability for its use or its suitability for particular application because of the product being used by the third party without our supervision. Any existing intellectual property right must be observed.